



2.5-inch U.2, 15mm, NVMe SSD
1.60TB, 1.92TB, 3.20TB, 3.84TB, 6.4TB, 7.68TB¹

Highlights

- Experience exceptional PCIe Gen5 performance in multiple capacities up to 7.68TB¹, perfect for compute-intensive applications
- Engineered for minimal power consumption, optimizing efficiency and reducing operational costs without compromising performance
- Achieve optimized solutions at low cost for your enterprise's mixed workloads with high-speed random read performance
- Delivering consistent QoS, even under heavy workloads, helping latency during mission-critical operations
- E1.S options also available, ensuring scalability and flexibility to meet your enterprise storage needs
- Benefit from enterprise-class features including Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, all backed by a 5-year limited warranty⁶

Applications/Environments

- AI Model Training and Inference, Machine Learning, Deep Learning
- Hyperscale Cloud and Enterprise Datacenters
- Compute Intensive Applications
- Standard Compute, High CPU, High GPU, HPC Workloads
- Big Data, Data Analytics, Data Modeling, Predictive Analysis

Redefining the limits for high-performance storage

Be ready for the future of mission critical workloads with the Western Digital Ultrastar DC SN861. The latest Western Digital SSD with cutting-edge PCIe[®] Gen5 enterprise-class speeds, the Ultrastar DC SN861 offers exceptional performance and multiple capacities up to 7.68TB¹. With high random read speeds and low power consumption, the DC SN861 is optimized for compute-intensive AI and machine learning applications, ensuring superior read/write performance, extremely low latency, and maximize IOPs/Watt. The DC SN861 also provides a rich feature set including NVMe[®] 2.0 and OCP 2.0 support, 1 & 3 DWPD, and a 5-year limited warranty⁶, making it the ideal solution for hyperscale, cloud, and enterprise data centers.

Features

Ready for the Demands of AI Workloads

Designed to handle compute-intensive AI and machine learning applications which require high bandwidths and low latencies.

Superior Performance and Capacity

Experience future-ready PCIe Gen5 read/write speeds with multiple capacities up to 7.68TB¹.

Designed for Power Efficiency

Architected to provide heightened performance per watt, optimizing power efficiency and reducing operational costs.

Outstanding Mixed Workload Performance

High-speed random reads provide enhanced solutions at low cost for your enterprise.

Optimized for Quality of Service (QoS)

Reduce latency during mission-critical workloads, delivering consistent Quality of Service (QoS) for your applications, even under heavy workloads.

Rich Enterprise Features

Benefit from enterprise-class features such as Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, helping ensure data integrity and security.

Future-Ready Data Infrastructure

Designed to support NVMe 2.0, and NVMe MI 1.2c, and OCP 2.0 supportive, for enhanced scalability and efficiency.

Ultrastar® DC SN861

DATA SHEET

DATA CENTER SOLID STATE DRIVE

Product Information

Capacity ¹	1.92TB	3.84TB	7.68TB	1.60TB	3.20TB	6.40TB
Endurance ²	1 DWPD	1 DWPD	1 DWPD	3 DWPD	3 DWPD	3 DWPD
Security	SE, ISE, TCG OPAL 2.01					
Form Factor	U.2					
Interface	PCIe Gen5x4					
NVMe Specification	NVMe v2.0					

Performance

Read Throughput (max MB/s, Seq 128KiB) ³	13,700	13,700	13,700	13,700	13,700	13,700
Write Throughput (max MB/s, Seq 128KiB) ³	3,600	7,200	7,500	3,600	7,200	7,500
Read IOPS (max, Rnd 4KiB) ³	2,100K	3,300K	3,300K	2,100K	3,300K	3,300K
Write IOPS (max, Rnd 4KiB) ³	165K	330K	430K	350K	665K	800K
Read Latency (μs) ⁴	65	65	65	65	65	65
Write Latency (μs) ⁴	8	8	8	8	8	8

Reliability

MTTF ⁵ (hours, projected)	2.5M
Uncorrectable Bit Error Rate (UBER)	1 in 10 ¹⁷
Annualized Failure Rate ⁵ (AFR, projected)	0.35%
Limited Warranty ⁶ (years)	5 years

Power Management

Requirement (DC, +/- 10%)	+12v
Operating Mode	12W, 14W, 16W, 18W, 20W (Default)
Idle (Average)	~5W

Physical Size

z-height (mm)	15mm
Dimensions (width x length, mm)	69.85mm x 100.45mm
Weight (g, max)	Not Available

Environmental

Operating Temperature (Ambient) ⁷	0°C to 70°C
Non-Operating Temperature ⁸	-40°C to 85°C

Ordering Information

	Region	Security	1.92TB	3.84TB	7.68TB	1.60TB	3.20TB	6.40TB
OTS Number	Worldwide	SE	OTS2516	OTS2517	OTS2518	OTS2537	OTS2538	OTS2539
Model Number	Worldwide	SE	WUS6BA119PSP9X1	WUS6BA138PSP9X1	WUS6BA176PSP9X1	WUS6CA216PSP9X1	WUS6CA232PSP9X1	WUS6CA264PSP9X1
OTS Number	Worldwide	ISE	OTS2525	OTS2526	OTS2527	OTS2531	OTS2532	OTS2533
Model Number	Worldwide	ISE	WUS6BA119PSP9X3	WUS6BA138PSP9X3	WUS6BA176PSP9X3	WUS6CA216PSP9X3	WUS6CA232PSP9X3	WUS6CA264PSP9X3
OTS Number	Worldwide	TCG Opal	OTS2528	OTS2529	OTS2530	OTS2534	OTS2535	OTS2536
Model Number	Worldwide	TCG Opal	WUS6BA119PSP9X7	WUS6BA138PSP9X7	WUS6BA176PSP9X7	WUS6CA216PSP9X7	WUS6CA232PSP9X7	WUS6CA264PSP9X7
OTS Number	China	SE	Not Applicable	OTS2520	OTS2521	Not Applicable	OTS2523	OTS2524
Model Number	China	SE	Not Applicable	WUS6BA138PSP9X1	WUS6BA176PSP9X1	Not Applicable	WUS6CA232PSP9X1	WUS6CA264PSP9X1

¹ One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB. Actual user capacity may be less due to operating environment.

² NAND Endurance.

³ Based on internal testing. Performance will vary by capacity point, or with the changes in useable capacity. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. IOPS = input/output operations persecond. Subject to change.

⁴ Average random latency at 4KiB, QD=1

⁵ MTTF and AFR specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model. MTTF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

⁶ The warranty for the product will expire on the earlier of (i) the date when the flash media has reached one-percent (1%) of its remaining life or (ii) the expiration of 5 years.

⁷ Composite temperature reading

⁸ Values are based on ambient temperature. Avoid non-operational exposure to temperatures in excess of 40°C for periods exceeding three months.



Western Digital

5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

Western Digital, the Western Digital design, the Western Digital logo, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe word mark is a trademark of NVM Express, Inc. PCIe is a registered trademark of PCI-SIG. All other marks are the property of their respective owners.

©2024 Western Digital Corporation or its affiliates. All rights reserved.

Product specifications subject to change without notice. Pictures shown may vary from actual products. References to Western Digital products do not imply they will be made available in all regions.