



E1.S, 15mm, NVMe SSD  
1.92TB, 3.84TB, 7.68TB<sup>1</sup>

## Highlights

- Experience exceptional PCIe Gen5 performance in multiple capacities up to 7.68TB<sup>1</sup>, perfect for compute-intensive applications
- Engineered for minimal power consumption, optimizing efficiency and reducing operational costs without compromising performance
- Achieve optimized solutions at low cost for your enterprise's mixed workloads with high-speed random read performance
- Delivering consistent QoS, even under heavy workloads, helping latency during mission-critical operations
- U.2 options also available, ensuring scalability and flexibility to meet your enterprise storage needs
- Benefit from enterprise-class features including Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, all backed by a 5-year limited warranty<sup>6</sup>

## Applications/Environments

- AI Model Training and Inference, Machine Learning, Deep Learning
- Hyperscale Cloud and Enterprise Datacenters
- Compute Intensive Applications
- Standard Compute, High CPU, High GPU, HPC Workloads
- Big Data, Data Analytics, Data Modeling, Predictive Analysis

## Redefining the limits for high-performance storage

Be ready for the future of mission critical workloads with the Western Digital Ultrastar DC SN861. The latest Western Digital SSD with cutting-edge PCIe Gen5 enterprise-class speeds, the Ultrastar DC SN861 offers exceptional performance and multiple capacities up to 7.68TB<sup>1</sup>. With high random read speeds and low power consumption, the DC SN861 is optimized for compute-intensive AI and machine learning applications, ensuring superior read/write performance, extremely low latency, and maximize IOPs/Watt available. The DC SN861 also provides a rich feature set including Flexible Data Placement (FDP), OCP 2.0 support, and a 5-year limited warranty<sup>6</sup>, making it the ideal solution for hyperscale, cloud, and enterprise data centers.

## Features

### Ready for the Demands of AI Workloads

Designed to handle compute-intensive AI and machine learning applications which require high bandwidths and low latencies.

### Superior Performance and Capacity

Experience future-ready PCIe Gen5 read/write speeds with multiple capacities up to 7.68TB<sup>1</sup>.

### Designed for Power Efficiency

Architected to provide heightened performance per watt, optimizing power efficiency and reducing operational costs.

### Outstanding Mixed Workload Performance

High-speed random reads provide enhanced solutions at low cost for your enterprise.

### Optimized for Quality of Service (QoS)

Reduce latency during mission-critical workloads, delivering consistent Quality of Service (QoS) for your applications, even under heavy workloads.

### Rich Enterprise Features

Benefit from enterprise-class features such as Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, helping ensure data integrity and security.

### Future-Ready Data Infrastructure

Designed with industry compliant NVMe™ 2.0<sup>10</sup>, and NVMe MI 1.2c, along with Flexible Data Placement (FDP)<sup>9</sup> and OCP 2.0 supportive, for enhanced scalability and efficiency.

# Ultrastar® DC SN861

## DATA SHEET

## DATA CENTER SOLID STATE DRIVE

Product Information			
Capacity <sup>1</sup>	1.92TB	3.84TB	7.68TB
Endurance <sup>2</sup>	1 DWPD		
Security	SE, ISE, TCG OPAL 2.01		
Form Factor	E1.S (15mm)		
Interface	PCIe® Gen5×4		
NVMe Specification	NVMe v1.4b		
Out-of-Band Management Support	Basic Management Over SMBUS		

Performance			
Read Throughput (max MB/s, Seq 128KiB) <sup>3</sup>	12,100	13,700	13,700
Write Throughput (max GB/s, Seq 128KiB) <sup>3</sup>	3,400	6,500	7,000
Read IOPS (max, Rnd 4KiB) <sup>3</sup>	1,550K	2,850K	2,850K
Write IOPS (max, Rnd 4KiB) <sup>3</sup>	140K	210K	235K
Read Latency (μs) <sup>4</sup>	70	70	70
Write Latency (μs) <sup>4</sup>	10	10	10

Reliability			
MTTF <sup>5</sup> (hours, projected)	2.5M		
Uncorrectable Bit Error Rate (UBER)	1 in 10 <sup>17</sup>		
Annualized Failure Rate <sup>5</sup> (AFR, projected)	0.35%		
Limited Warranty <sup>6</sup> (years)	5 years		

Power Management			
Requirement (DC, +/- 10%)	+12v	+12v	+12v
Operating Modes (avg, max)	12W	21W	21W
Idle (Average)	< 5W	< 5W	< 5W

Physical Size			
z-height (mm)	15mm		
Dimensions (width x length, mm)	33.75mm x 118.75mm		
Weight (g, max)	95g		

Environmental			
Operating Temperature (Ambient) <sup>7</sup>	0°C to 70°C		
Worst Case Airflow to reach max performance in 30°C	1.5 meters per second at sea level		
Non-Operating Temperature <sup>8</sup>	-40°C to 85°C		

Ordering Information				
	Security	1.92TB	3.84TB	7.68TB
OTS Number	SE	OTS2569	OTS2570	OTS2571
Model Number	SE	WUS6A7619PKP8X1	WUS6A7638PKP8X1	WUS6A7676PKP8X1
OTS Number	ISE	OTS2572	OTS2573	OTS2574
Model Number	ISE	WUS6A7619PKP8X3	WUS6A7638PKP8X3	WUS6A7676PKP8X3
OTS Number	TCG Opal	OTS2566	OTS2567	OTS2568
Model Number	TCG Opal	WUS6A7619PKP8X7	WUS6A7638PKP8X7	WUS6A7676PKP8X7

<sup>1</sup> One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB. Actual user capacity may be less due to operating environment.

<sup>2</sup> NAND Endurance.

<sup>3</sup> Based on internal testing. Performance will vary by capacity point, or with the changes in useable capacity. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. IOPS = input/output operations persecond. Subject to change.

<sup>4</sup> Average random read latency at 4KiB, QD=1

<sup>5</sup> MTTF and AFR specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model. MTTF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

<sup>6</sup> The warranty for the product will expire on the earlier of (i) the date when the flash media has reached one-percent (1%) of its remaining life or (ii) the expiration of 5 years.

<sup>7</sup> Composite temperature reading

<sup>8</sup> Values are based on ambient temperature. Avoid non-operational exposure to temperatures in excess of 40°C for periods exceeding three months.

<sup>9</sup> Flexible Data Placement (FDP) available on E1.S device only.

<sup>10</sup> Only available on U.2 form factor.



5601 Great Oaks Parkway  
San Jose, CA 95119, USA  
www.westerndigital.com

Western Digital, the Western Digital design, the Western Digital logo, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. The NVMe word mark is a trademark of NVM Express, Inc. PCIe is a registered trademark of PCI-SIG. All other marks are the property of their respective owners.

©2024 Western Digital Corporation or its affiliates. All rights reserved.

Product specifications subject to change without notice. Pictures shown may vary from actual products. References to Western Digital products do not imply they will be made available in all regions.